



SEDIMAX™
SEDIMENT RETENTION

Specification Sheet SediMax-WS9™ (Straw Wattle 9 Inch)

DESCRIPTION

The SediMax-SW9 shall be composed of 100% agricultural straw and be wrapped in tubular UV stabilized synthetic net.

The netting weight shall be approximately 0.35 ounces/linear ft. and shall be made from HDPE (High Density Polyethylene) photodegradable oriented net with carbon black for UV inhibition. The netting shall have a diamond shaped aperture measuring 0.50 x 0.50 inches (1.27 x 1.27 cm).

The wattle ends will be secured with wire closures. SediMax-SW9 shall be installed according to manufacturer's recommendations. They shall be installed on contours and staked with 18 to 24 inch wood stakes at four foot on center.



Material Content

| | | |
|---------------------|--------------------------------------|---|
| Matrix | 100% Straw Fiber | 2.4 lbs/linear ft (3.54 kg/linear meter) |
| Netting | Tubular, diamond-shaped netting | 0.35 oz/linear ft (30.0 g/linear meter) |
| Wire Closure | Industrial grade ring wire, 18 gauge | 3.75 in (9.53 cm) |

Physical Specifications

| | |
|-----------------------|----------------------|
| Width | 9.00 in (22.86 cm) |
| Length | 25.00 ft (7.62 m) |
| Weight +/- 10% | 60.00 lbs (27.22 kg) |



Western Green
4609 E. Boonville-New Harmony Rd.
Evansville, IN 47725

nagreen.com
800-772-2040

©2019, North American Green is a registered trademark from Western Green. Certain products and/or applications described or illustrated herein are protected under one or more U.S. patents. Other U.S. patents are pending, and certain foreign patents and patent applications may also exist. Trademark rights also apply as indicated herein. Final determination of the suitability of any information or material for the use contemplated, and its manner of use, is the sole responsibility of the user. Printed in the U.S.A.