MATERIAL PROPERTY DATA SHEET



Coir Mat 400

Long Term • Coconut Net • Biodegradable • Erosion Control Blanket

DESCRIPTION

The coir fiber blankets are made from hand from the highest quality coir available on the market. The coir fiber is twisted into a high strength rope and then woven into the matting. Coir mats are made from 100% natural and biodegradable coir to be used to hold seed and soil during the establishment of a vegetative cover.



| Material Content | | | | |
|------------------|---|--|--|--|
| Yarn | Wheel spun, weed cleaned, evenly spun and uniformly twisted | | | |
| Netting Weight | (400 g/ sm) | | | |

| Standard Roll Sizes | | | | | | |
|---------------------|--------|----------|---------|----------|--|--|
| Width | 6.6 ft | (2 m) | 13.1 ft | (4 m) | | |
| Length ± 10% | 164 ft | (50 m) | 164 ft | (50 m) | | |
| Weight ± 10%* | 88 lbs | (40 kg) | 176 lbs | (80 kg) | | |
| Area | 120 SY | (100 sm) | 240 SY | (200 sm) | | |

| Index Property | Test Method | Typical | |
|------------------------------|-------------|------------|-------------|
| Thickness | ASTM D6525 | 0.35 in. | (9 mm) |
| Mass/Unit Area | ASTM D3776 | 13 oz/sy | (400 g/ sm) |
| Open Area | | 65% | |
| Tensile Strength – MD | ASTM D4595 | 780 lbs/ft | (11.5 kN/m) |
| Elongation – MD | ASTM D4595 | 35% | |
| Tensile Strength – TD | ASTM D4595 | 560 lbs/ft | (8.2 kN/m) |
| Elongation – TD | ASTM D4595 | 30% | |
| Recommended Flow Velocity | | 8 ft/s | 2.4 m/s |
| C Factor, 1.5:1 Slope | | N/A | |
| Life Expectancy | | 36 Months | |

Disclaimer: The information contained herein may represent product index data, performance ratings, bench scale testing or other material utility quantifications. Each representation may have unique utility and limitations. Every effort has been made to ensure accuracy, however, no warranty is claimed and no liability shall be assumed by Western Green or its affiliates regarding the completeness, accuracy or fitness of these values for any particular application or interpretation. While testing methods are provided for reference, values shown may be derived from interpolation or adjustment to be representative of intended use. For further information, please feel free to contact Western Green.

©2023, Western Green. Certain products and/or applications described or illustrated herein are protected under one or more U.S. patents. Other U.S. patents are pending, and certain foreign patents and patent applications may also exist. Trademark rights also apply as indicated herein. Final determination of the suitability of any information or material for the use contemplated, and its manner of use, is the sole responsibility of the user. Printed in the U.S.A.



Rev. 4.2023 Scan for additional and updated product information

